

INTELIGENTE ALTA FRECUENCIA HF Plus

MODELO	V A	MARCA	ORIGEN	VCA	TIEMPO DE CARGA DE SU BATERIA (Ah)				MEDIDAS (L x P x H) mm	PESO Kg
					5,34 Hs Ah C ₅	8 Hs Ah C ₅	5,34 Hs Ah C ₈	8 Hs Ah C ₈		
HF Plus 1224-40-2	12 -24V 40A	Micropower	Suecia	220-240V	200	333	228	380	256 x 243 x 417	5.1
HF Plus 243648-40-2	24-36-48V 40A	Micropower	Suecia	220-240V	200	333	228	380	256 x 229 x 529	7.2
HF Plus 243648-60-2	24-36-48V 60A	Micropower	Suecia	220-240V	300	500	342	570	256 x 229 x 529	7.8
HF Plus 2436487280-60-3	24-36-48-72-80V 60A	Micropower	Suecia	380-415V	300	500	342	570	256 x 243 x 417	16.2
HF Plus 1224-80 -2	12 -24V 80A	Micropower	Suecia	220-240V	400	665	456	758	256 x 243 x 529	7.2
HF Plus 243648-80-3	24-36-48V 80A	Micropower	Suecia	380-440V	400	665	456	758	266 x 152 x 387	9.1
HF Plus 2436487280-80-3	24-36-48-72-80V 80A	Micropower	Suecia	380-415V	400	665	456	758	256 x 243 x 417	17
HF Plus 1224-100-3	12-24V 100A	Micropower	Suecia	380-440V	500	833	570	950	266 x 152 x 387	9.7
HF Plus 243648-100-3	24-36-48V 100A	Micropower	Suecia	380-415V	500	833	570	950	266 x 152 x 387	17.4
HF Plus 2436487280-100-3	24-36-48-72-80V 100A	Micropower	Suecia	380-415V	500	833	570	950	256 x 243 x 417	17.6
HF Plus 2436-105-3	24-36V 105A	Micropower	Suecia	380-440V	525	875	598	998	266 x 152 x 387	9.7
HF Plus 1224-130-3	12-24V 130A	Micropower	Suecia	380-440V	650	1083	741	1235	266 x 152 x 387	10.6
HF Plus 243648-130-3	24-36-48V 130A	Micropower	Suecia	380-415V	650	1083	741	1235	266 x 152 x 387	18.4
HF Plus 1224-150-3	12-24V 150A	Micropower	Suecia	380-415V	750	1250	855	1425	256 x 243 x 417	18.2
HF Plus 243648-165-3	24-36-48V 165A	Micropower	Suecia	380-415V	824	1374	940	1566	256 x 243 x 417	18.4
HF Plus 1224-200-3	12-24V 200A	Micropower	Suecia	380-415V	1000	1665	1140	1898	256 x 243 x 529	23.2
HF Plus 122436-200-3	12-24-36V 200A	Micropower	Suecia	380-415V	1000	1665	1140	1898	256 x 243 x 529	21.4
HF Plus 243648-200-3	24-36-48V 200A	Micropower	Suecia	380-415V	1000	1665	1140	1898	256 x 459 x 659	42

INTELIGENTE ALTA FRECUENCIA HF

MODELO	V A	MARCA	ORIGEN	VCA	TIEMPO DE CARGA DE SU BATERIA (Ah)				MEDIDAS (L x P x H) mm	PESO Kg
					5,34 Hs Ah C ₅	8 Hs Ah C ₅	5,34 Hs Ah C ₈	8 Hs Ah C ₈		
HF 12-20-2	12V 20A	Micropower	Suecia	220-240V	92	153	105	174	112 x 74 x 243	2.1
HF 24-20-2	24V 20A	Micropower	Suecia	220-240V	92	153	105	174	112 x 74 x 243	2.1
HF 24-30-2	24V 30A	Micropower	Suecia	220-240V	138	230	157	262	112 x 74 x 243	2.1
HF 48-30-2	48V 30A	Micropower	Suecia	220-240V	138	230	157	262	138 x 89 x 295	3.1
HF 36-40-2	36V 40A	Micropower	Suecia	220-240V	184	306	209	349	138 x 89 x 295	3.1
HF 48-40-2	48V 40A	Micropower	Suecia	220-240V	200	333	228	380	256 x 243 x 529	7.2
HF 24-45-2	24V 45A	Micropower	Suecia	220-240V	207	345	236	393	138 x 89 x 295	3.1
HF 24-60-2	24V 60A	Micropower	Suecia	220-240V	275	459	314	523	138 x 89 x 295	3.1

INTELIGENTE ALTA FRECUENCIA HF

MODELO	V A	MARCA	ORIGEN	VCA	TIEMPO DE CARGA DE SU BATERIA (Ah)				MEDIDAS (L x P x H) mm	PESO Kg
					5,34 Hs Ah C ₅	8 Hs Ah C ₅	5,34 Hs Ah C ₈	8 Hs Ah C ₈		
HF 487280-60-3	48-72-80V 60A	Micropower	Suecia	380-415V	300	500	342	570	256 x 243 x 417	16.1
HF 1224-80-3	12-24V 80A	Micropower	Suecia	380-440V	400	665	456	758	266 x 152 x 387	9.1
HF 24-80-2	24V 80A	Micropower	Suecia	220-240V	400	665	456	758	266 x 152 x 387	7.2
HF 243648-80-3	24-36-48V 80A	Micropower	Suecia	380-440V	400	665	456	758	266 x 152 x 387	9.1
HF 487280-80-3	48-72-80V 80A	Micropower	Suecia	380-415V	400	665	456	758	256 x 243 x 417	17
HF 1224-100-3	12-24V 100A	Micropower	Suecia	380-440V	500	833	570	950	266 x 152 x 387	9.7
HF 24-100-2	24V 100A	Micropower	Suecia	220-240V	500	833	570	950	266 x 152 x 387	7.8
HF 243648-100-3	24-36-48V 100A	Micropower	Suecia	380-415V	500	833	570	950	266 x 152 x 387	17.3
HF 487280-100-3	48-72-80V 100A	Micropower	Suecia	380-415V	500	833	570	950	256 x 243 x 417	17.6
HF 2436-105-3	24-36V 105A	Micropower	Suecia	380-440V	525	875	598	998	266 x 152 x 387	9.7
HF 1224-130-3	12-24V 130A	Micropower	Suecia	380-440V	650	1083	741	1235	266 x 152 x 387	10.6
HF 243648-130-3	24-36-48V 130A	Micropower	Suecia	380-415V	650	1083	741	1235	266 x 152 x 387	18.4
HF 1224-150-3	12-24V 150A	Micropower	Suecia	380-415V	750	1250	855	1425	256 x 243 x 417	18.2
HF 2436-150-3	24-36V 150A	Micropower	Suecia	380-415V	750	1250	855	1425	256 x 243 x 417	18.4
HF 243648-165-3	24-36-48V 165A	Micropower	Suecia	380-415V	824	1374	940	1566	256 x 243 x 417	18.4
HF 1224-200-3	12-24V 200A	Micropower	Suecia	380-415V	1000	1665	1140	1898	256 x 243 x 529	23

AUTOMATICO WA

MODELO	V A	MARCA	ORIGEN	VCA	TIEMPO DE CARGA DE SU BATERIA (Ah)				MEDIDAS (L x P x H) mm	PESO Kg
					5,34 Hs Ah C ₅	8 Hs Ah C ₅	5,34 Hs Ah C ₈	8 Hs Ah C ₈		
WA 12-10-2	12V 10A	TAO Power	Argentina	220V	-	-	-	100	400 x 270 x 285	14
WA 12-20-2	12V 20A	TAO Power	Argentina	220V	-	-	-	150	400 x 270 x 285	15
WA 12-20-2 SP	12V 20A	TAO Power	Argentina	220V	-	-	-	150	400 x 270 x 285	15
WA 24-25-2	24V 25A	TAO Power	Argentina	220V	-	-	-	150	400 x 270 x 285	19
WA 12-30-2	12V 30A	TAO Power	Argentina	220V	-	-	-	170	400 x 270 x 285	16
WA 24-30-2	24V 30A	TAO Power	Argentina	220V	-	-	-	170	400 x 270 x 285	21
WA 24-30-2 SP	24V 30A	TAO Power	Argentina	220V	-	-	-	170	400 x 270 x 285	21
WA 12-40-2	12V 40A	TAO Power	Argentina	220V	-	-	-	220	400 x 270 x 285	18
WA 12-40-2 SP	12V 40A	TAO Power	Argentina	220V	-	-	-	220	400 x 270 x 285	18
WA 24-40-2	24V 40A	TAO Power	Argentina	220V	-	-	-	220	400 x 270 x 285	24

AUTOMATICO WA

MODELO	V A	MARCA	ORIGEN	VCA	TIEMPO DE CARGA DE SU BATERIA (Ah)				MEDIDAS (L x P x H) mm	PESO Kg
					5,34 Hs Ah C ₅	8 Hs Ah C ₅	5,34 Hs Ah C ₈	8 Hs Ah C ₈		
WA 24-40-2 SP	24V 40A	TAO Power	Argentina	220V	-	-	-	220	400 x 270 x 285	24
WA 48-40-3	48V 40A	TAO Power	Argentina	380V	-	-	-	220	425 x 390 x 582	47
WA 24-50-2	24V 50A	TAO Power	Argentina	220V	-	-	-	275	400 x 270 x 285	27
WA 24-50-2 SP	24V 50A	TAO Power	Argentina	220V	-	-	-	275	400 x 270 x 285	27
WA 48-50-3	48V 50A	TAO Power	Argentina	380V	-	-	-	299	425 x 390 x 582	52
WA 12-60-2	12V 60A	TAO Power	Argentina	220V	-	-	-	300	400 x 270 x 285	20
WA 24-60-2	24V 60A	TAO Power	Argentina	220V	-	-	-	300	400 x 270 x 285	30
WA 24-60-3	24V 60A	TAO Power	Argentina	380V	-	-	-	350	425 x 390 x 582	33
WA 36-60-3	36V 60A	TAO Power	Argentina	380V	-	-	-	375	425 x 390 x 582	56
WA 48-60-3	48V 60A	TAO Power	Argentina	380V	-	-	-	375	425 x 390 x 582	64
WA 72-60-3	72V 60A	TAO Power	Argentina	380V	-	-	-	375	530 x 490 x 760	105
WA 12-80-2	12V 80A	TAO Power	Argentina	220V	-	-	-	400	400 x 270 x 285	24
WA 24-80-3	24V 80A	TAO Power	Argentina	380V	-	-	-	450	425 x 390 x 582	56
WA 48-80-3	48V 80A	TAO Power	Argentina	380V	-	-	-	450	530 x 490 x 760	86
WA 72-80-3	72V 80A	TAO Power	Argentina	380V	-	-	-	450	530 x 490 x 760	116
WA 80-80-3	80V 80A	TAO Power	Argentina	380V	-	-	-	450	530 x 490 x 760	130
WA 12-100-3	12V 100A	TAO Power	Argentina	380V	-	-	-	550	425 x 390 x 582	30
WA 24-100-3	24V 100A	TAO Power	Argentina	380V	-	-	-	550	425 x 390 x 582	61
WA 48-100-3	48V 100A	TAO Power	Argentina	380V	-	-	-	550	530 x 490 x 760	95
WA 72-100-3	72V 100A	TAO Power	Argentina	380V	-	-	-	550	550 x 550 x 830	125
WA 80-100-3	80V 100A	TAO Power	Argentina	380V	-	-	-	550	550 x 550 x 830	135
WA 12-120-3	12V 120A	TAO Power	Argentina	380V	-	-	-	650	425 x 390 x 582	44
WA 24-120-3	24V 120A	TAO Power	Argentina	380V	-	-	-	650	425 x 390 x 582	66
WA 36-120-3	36V 120A	TAO Power	Argentina	380V	-	-	-	650	530 x 490 x 760	80
WA 48-120-3	48V 120A	TAO Power	Argentina	380V	-	-	-	650	530 x 490 x 760	101
WA 72-120-3	72V 120A	TAO Power	Argentina	380V	-	-	-	650	550 x 550 x 830	130
WA 80-120-3	80V 120A	TAO Power	Argentina	380V	-	-	-	650	550 x 550 x 830	143
WA 12-140-3	12V 140A	TAO Power	Argentina	380V	-	-	-	780	425 x 390 x 582	48
WA 24-140-3	24V 140A	TAO Power	Argentina	380V	-	-	-	780	530 x 490 x 760	67
WA 36-140-3	36V 140A	TAO Power	Argentina	380V	-	-	-	780	530 x 490 x 760	90
WA 48-140-3	48V 140A	TAO Power	Argentina	380V	-	-	-	780	530 x 490 x 760	120

AUTOMATICO WA

MODELO	V A	MARCA	ORIGEN	VCA	TIEMPO DE CARGA DE SU BATERIA (Ah)				MEDIDAS (L x P x H) mm	PESO Kg
					5,34 Hs Ah C ₅	8 Hs Ah C ₅	5,34 Hs Ah C ₈	8 Hs Ah C ₈		
WA 72-140-3	72V 140A	TAO Power	Argentina	380V	-	-	-	780	550 x 550 x 830	168
WA 80-140-3	80V 140A	TAO Power	Argentina	380V	-	-	-	780	550 x 550 x 830	175
WA 12-160-3	12V 160A	TAO Power	Argentina	380V	-	-	-	880	425 x 390 x 582	52
WA 24-160-3	24V 160A	TAO Power	Argentina	380V	-	-	-	880	530 x 490 x 760	70
WA 36-160-3	36V 160A	TAO Power	Argentina	380V	-	-	-	880	530 x 490 x 760	95
WA 48-160-3	48V 160A	TAO Power	Argentina	380V	-	-	-	880	530 x 490 x 760	116
WA 80-160-3	80V 160A	TAO Power	Argentina	380V	-	-	-	880	550 x 550 x 830	187
WA 12-180-3	12V 180A	TAO Power	Argentina	380V	-	-	-	970	425 x 390 x 582	56
WA 24-180-3	24V 180A	TAO Power	Argentina	380V	-	-	-	970	530 x 490 x 760	74
WA 36-180-3	36V 180A	TAO Power	Argentina	380V	-	-	-	970	530 x 490 x 760	103
WA 48-180-3	48V 180A	TAO Power	Argentina	380V	-	-	-	970	530 x 490 x 760	132
WA 24-200-3	24V 200A	TAO Power	Argentina	380V	-	-	-	1100	530 x 490 x 760	80
WA 36-200-3	36V 200A	TAO Power	Argentina	380V	-	-	-	1100	530 x 490 x 760	118
WA 48-200-3	48V 200A	TAO Power	Argentina	380V	-	-	-	1100	530 x 490 x 760	145
WA 24-220-3	24V 220A	TAO Power	Argentina	380V	-	-	-	1200	530 x 490 x 760	85
WA 36-220-3	36V 220A	TAO Power	Argentina	380V	-	-	-	1200	530 x 490 x 760	122
WA 80-260-3	80V 260A	TAO Power	Argentina	380V	-	-	-	1450	ESPECIAL	ESPECIAL

AUTOMATICO FONDO FLOTE

MODELO	V A	MARCA	ORIGEN	VCA
FF 12-20-2	12V 20A	TAO Power	Argentina	220V
FF 1224-20-2	12 24V 20A	TAO Power	Argentina	220V
FF 1224-80-2	12 24V 80A	TAO Power	Argentina	220V
FF 24-20-2	24V 20A	TAO Power	Argentina	220V
FF 24-25-2	24V 25A	TAO Power	Argentina	220V

AUTOMATICO FONDO FLOTE

MODELO	V A	MARCA	ORIGEN	VCA
TI-IUI-24-25-2	24V 25A	TAO Power	Argentina	220V
TI-IUI-48-20-2	48V 20A	TAO Power	Argentina	220V